

SPG300 SERIES



FEATURE:

- International AC Input Range
- Soft-Start Circuit, Limiting AC Surge
- Protection: Short circuit/Over load/Over voltage/Over temperature
- Built in EMI Filter, Low Ripple Noise
- Built in PFC Circuit to meet IEC61000-3-2
- Compliance to UL1950, EN60950
- Forced air cooling by build-in DC fan
- MTBF 100Khrs Min., MIL-HDBK-217F (25°C)
- Remote On/Off Control (Option)
- Provide parallel connection function
- 100% Full Load Burn-in Test
- Three Years Warranty

SPECIFICATIONS:

Model		SPG300-5V~TSP300-54V		
Voltage Range		AC90-264V(1ϕ) or DC100-340V		
INPUT	AC Current	V _{in} =100VAC	4.4A typ	
		V _{in} =200VAC	2.2A typ	
	Frequency	47~63 Hz		
	Efficiency	80~87% typ		
	Power Factor	V _{in} =100VAC	0.99typ (I _o =100%)	
		V _{in} =200VAC	0.95typ (I _o =100%)	
	Inrush Current	V _{in} =100VAC	20 Atyp (I _o =100%,At cold state)	
		V _{in} =200VAC	40 Atyp (I _o =100%,At cold state)	
Leakage Current	1.0mA max (60Hz,According to UL,CSA,VDE AND DEN-AN)			
OUTPUT	DC Voltage	5~54VDC		
	Current	50~5.6 A		
	Line Regulation	20~190mV max		
	Load Regulation	40~300mV max		
	Ripple	0~+50°C*1	80~150mVp-p max	
		-10~0°C*1	140~200mVp-p max	
	Ripple Noise	0~+50°C*1	120~400mVp-p max	
		-10~0°C*1	160~600mVp-p max	
	Temperature Regulation	0~+50°C	50~500 mV max	
		-10~0°C	60~600 mV max	
	Drift *2	20~192 mV max		
	Start-Up Time	500mS max (V _{in} =85VAC, I _o =100%)		
Hold-Up Time	20mS typ (I _o =100%)			
Output Voltage Adjustment Range	±10%			
PROTECTION CIRCUIT AND OTHERS	Over Current Protection	Work over 105% of rating and recovers automatically		
	Over Voltage Protection	Works at 115-140% of rating		
	Operating Indication	LED(GREEN)		
	Remote Sensing	Provided		
Remote ON/OFF	Optional(Refer to Instruction Manual)			
ISOLATION	Input-Output.RC*3	AC3000V 1minute, Cutoff current=20mA, DC500V 50MΩ min (At room temperature)		
	Input-FG	AC2000V 1minute, Cutoff current=20mA, DC500V 50MΩ min (At room temperature)		
	Output.RC-FG*3	AC500V 1minute, Cutoff current=100mA, DC500V 50MΩ min (At room temperature)		
	Output-RC*3	AC100V 1minute, Cutoff current=100mA, DC100V 10MΩ min (At room temperature)		
ENVIRONMENT	Operating Temperature, Humidity and Altitude	-10~+65°C, 20~90% RH(Non condensing)(Refer to DERATION CURVE), 3,000m(10,000feet)max		
	Storage Temperature, Humidity and Altitude	-20~+75°C, 20~90% RH(Non condensing), 9,000m(3,000feet)max		
	Vibration	10~55HZ, 19.6m/s ² (2G), 3minutes period, 60minutes each along X,Y and Z axis		
	Impact	196.1m/s ² (20G), 11ms, once each X,Y and Z axis		
Safety and Noise Regulations	Safety Standard	Compliance to UL1950,EN60950,VDE0160,CSA C22.2 N0.234Complies with DEN-AN and IEC60950		
	Conducted Emission	Compliance to FCC-B,CISPR22-B,EN55022-B,VCCI-B		
	Radiated Emission	Compliance to FCC-B,CISPR22-B,EN55022-B,VCCI-B		
	Harmonic Attenuator	Compliance to IEC61000-3-2		
OTHERS	Case Size	50×124.5×214.5mm (without terminal block)(W×H×D)		
	Weight	2200g max		
	Cooling Method	Forced cooling (internal fan)		

*1: According to 20MHz oscilloscope or Ripple-Nose meter (equivalent to KEISKU-GIKEN: RM101)

*2: Drift is change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

*3: Applicable when Remote ON/OFF (optional) is added

